



16" Turning Radius

Tightest turning radius of any garden tractor providing the ultimate in maneuverability.



Arc-Welded Steel Chassis

Provides added strength and rigidity for demanding, ground-engaging applications.



Unmatched Versatility

Conversion kits available for Toro Classic or 260 owners for use with existing implements.



*See your dealer for details on warranties and special features.

400XT SERIES

Toro® Wheel Horse® 400XT Series Garden Tractors

Traditional quality, exceptional performance.



Count on it.

400XT

SERIES

SPECIFICATIONS



GT410

GT420

GT430

Engine	Kohler® Command	Kawasaki®	Kawasaki
Displacement	460cc	585cc	585cc
Construction	OHV Hydraulic Valve Lifters Full-Pressure Lubrication	Twin-Cylinder OHV Hydraulic Valve Lifters Full-Pressure Lubrication	Twin-Cylinder OHV Hydraulic Valve Lifters Full-Pressure Lubrication
Make	Hydro-Gear	Hydro-Gear	Hydro-Gear
Type	Hydrostatic	Hydrostatic	Hydrostatic
Ground Speed - Fwd	0 - 6.9 mph	0 - 6.9 mph	0 - 6.9 mph
Ground Speed - Rev	0 - 3.4 mph	0 - 3.4 mph	0 - 3.4 mph
KeyChoice™ System	Standard	Standard	Standard
Cast-Iron Front Axle	Standard	Standard	Standard
Headlights	Standard	Standard	Standard
Indicator Lights	PTO, KeyChoice	Alternator, Oil Pressure PTO, KeyChoice	Alternator, Oil Pressure PTO, KeyChoice Low Fuel, Cruise
Gauges	Hour meter	Hour meter	Hour meter
Cruise Control	Optional	Standard	Standard
Steering	14" Comfort Grip™ w/Tilt Steering	14" Soft Touch™ w/Tilt Steering	14" Soft Touch w/Tilt Steering
Cupholder	Standard	Standard	Standard
Tires	16 x 6.5 Front 4-ply 23 x 10.5 Rear 4-ply	16 x 6.5 Front 4-ply 23 x 10.5 Rear 4-ply	16 x 6.5 Front 4-ply 23 x 10.5 Rear 4-ply
Attachment Lift	Manual	Manual	Power
Warranty**	5-Year Workhorse™ on frame & axle 2-Year Full	5-Year Workhorse on frame & axle 2-Year Full	5-Year Workhorse on frame & axle 2-Year Full
Wheelbase	49.5"	49.5"	49.5"
Width	36.0"	36.0"	36.0"
Length	69.2"	69.2"	69.2"
Weight (lbs w/o deck)	631	657	657
Fuel Capacity	4 Gallons	4 Gallons	4 Gallons
Turning Radius	16"	16"	16"
Height of Cut	1" - 4"	1" - 4"	1" - 4"
Mowing Decks	42" Rear Discharge 42", 48" Side Discharge 48" Recycler®	42" Rear Discharge 42", 48", 52" Side Discharge 48", 52" Recycler	42" Rear Discharge 42", 48", 52" Side Discharge 48", 52" Recycler

1 RECYCLER® MOWING DECKS
Optional Recycler decks cut and recut grass clippings, nourishing your lawn with a fine mulch.

2 ATTACH-A-MATIC SYSTEM
Premium hitch system enables quick and easy no-tools attachment of accessories.

3 KEYCHOICE SYSTEM
Toro's exclusive KeyChoice Reverse Operation System improves safety during operation in reverse, without diminishing performance.

4 5-YEAR WORKHORSE WARRANTY
Industry leading 5-Year warranty on frame, and axle.

Toro has taken great care to match the power capacity of the engine on this product with the requirements of the application.